



Male Gas Threaded


Size	Ø B	L	Valve Material	O-Ring Material	Code
1/4"	6,00	38,00	1.4404	FPM/FKM	022Z60025V
				EPDM	022Z60025EP
				SILICONE FDA	022Z60025SIF

Int. finishing: $Ra \leq 1,2 \mu m$ Ext. finishing: $Ra \leq 1,6 \mu m$ mirror polished


Max Working Conditions:

6 bar (87 psi) and 150°C (300°F)

Installation:

Horizontal installation recommended

Spare parts



N°	Name	Material
1	Body	AISI 316L
2	Piston	AISI 316L
3	O-Ring 2025	FPM/FKM or EPDM or SILICONE FDA
4	M3 Screw	AISI 304
5	Handle	AISI 316L
6	Seeger	AISI 304

N°	Description	Valve size	Code
2	Piston - n° 1 pcs	all sizes	AAAA0381
3	O-Ring Kit 2025 FPM/FKM - n° 5 pcs	all sizes	ORNSV05V
3	O-Ring Kit 2025 EPDM - n° 5 pcs	all sizes	ORNSV05EP
3	O-Ring Kit 2025 SILICONE FDA - n° 5 pcs	all sizes	ORNSV05SIF
5	Handle - n° 1 pcs	all sizes	AAAA0380
6	Seeger - n° 10 pcs	all sizes	SEEGERSV