


TECHNICAL INFORMATION _ CAT. N. YACT SEND 0XC0 X0000

CABLE FOR DOUBLE POS. SENSOR



.....

Clean and Aseptic Valves of CAD Product Line have simple and safe design, with their full drainability, without asymptotic seal and dead leg, are offering fast cleanability and sterilization practices. They are designed to fulfill stringent demands of CIP-SIP and Production Cycles on Aseptic Processing.

Cable for CAD Double Position Sensor, genuine cable to provide power supply to CAD Sensor, arrange remote programming via PLC and transmit open and close position of the actuator where sensor is installed.

.....

CODE	SUITABLE FOR CAD SENSOR	Lenght mm (inch)
YACT-SEND-0XC0-X0000	XACT-SEND-0XX0-X0000	4,00 (157)

SPECIFICATION:

MATERIAL	PVC
-----------------	-----

Design Temperature: -10 to 60 °C (14 to 140 °F)

Application Areas: SAFE

Packaging: CAD Cable is sealed in plastic bags and packaged in a closed box

Quality Control: Quality Assurance System guarantees the control and traceability of the product.

Orders and Information: For additional information or to place a order call your nearest Distributor or visit www.rattiinox.com

**CONNECTION DIAGRAM
5 POLES FEMALE**

